





TouchPro™ Pro-G Glass PCAP

10" to 27" Touch Solution



16 pt Multi-Touch




Up to 27" (Standard Format)



2 Glass Solution (2GS)

Product Overview

The Elo TouchPro Pro-G Projected Capacitive (PCAP) touch technology offers a fast and sensitive response and professional-grade reliability combined with a stylish, sleek design. Elo's Pro-G PCAP is designed for the rigors of commercial applications. The glass-glass solution (2GS) offers pristine optical clarity, high touch durability and long term stability over temperature. Pro-G is available in standard screen sizes up to 27-inches with 10-point multi-touch capabilities. Elo's TouchPro line offers a complete PCAP solution including touch screen, controller, drivers for various operating systems and software utilities resulting in shorter development and integration time. The complete integration guide provides guidelines to simplify integration and avoid typical issues such as EMI from sources such as the power supply or LCD screen. Elo also offers a wide range of customization options to meet your requirements including screen dimensions, cover glass thickness, LCD bonding, branding and surface treatments such as anti-glare.



Controller

8300-Series 24" - 70"

8200-Series up to 22"

Elo TouchPro Pro-G Glass Projected Capacitive Specifications

Touchscreen	
Size Range	7" to 27"
Light Transmittance	≥ 90%
Haze	< 1%
Overall Thickness	3.1mm
Cover Glass	1.8mm
Durability	Over 50 million touches in one location
Sealing	Can be sealed to meet NEMA 4, NEMA 12 and IP 65 standards

Touch Performance	
Input Methods	Finger, gloved hand, or passive stylus
Number of Touches	Up to 10
Response Time	25ms (15ms secondary)
Report Rate	> 100Hz
Latency	< 25ms
Positional Accuracy	± 2.5mm
Resolution	4096 x 4096
Touch Activation Force	Zero

Electrical	
Communication Interface(s)	USB (Standard), I2C, HID Over I2C (Optional)
Power Supply Voltage Requirements	5V (USB)
Current - Operating Mode	Typical 58mA

Environmental	
Touchscreen	Operating Temp -20 to 70C (Non Condensing) Storage Temp -40 to 85C (Non Condensing)
Controller	Operating Temp -20 to 70C (Non Condensing) Storage Temp -40 to 85C (Non Condensing)
Safety Approvals	UL

Software	
Operating Systems	Windows XP, Windows 7, Windows 8, Linux, Android
Utilities	Multiple monitor, various touch modes, touch zones

Warranty	
2 year limited warranty	

Benefits	
16-point multi-touch	
Fast and sensitive touch response	
Excellent optical clarity	
Long-term stable operation over temperature	
Optional surface treatments such as anti-glare	

Applications	
Interactive digital signage	
Gaming and lottery terminals	
Industrial automation	
Medical equipment	
Point-of-information & transportation kiosks	
POS solutions	
Education/white board	
Self-service/service automation	

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America

Tel +1 408 597 8000
Fax +1 408 597 8050
elosales.na@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel +1 786-923-0251
Fax +1 305-931-0124
elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo and the Elo logo are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17042AES00081

