



NOTE:

1. ALL DIMENSIONS ARE IN MILLIMETERS.  
THE UNSPECIFIED DIMENSION TOLERANCES ARE PLUS/MINUS 0.5.  
ACTIVE AREA DIMENSIONS: 306(L) × 230(W)  
VIEWABLE AREA DIMENSIONS: 306(L) × 230(W)  
PROFILE DIMENSIONS: 349.5(L) × 273.5(W) × 8.2(D).  
2. SPECIFICATION:
- ① TECHNICS HOLE:  $6 - \phi 2.5$ .
  - ② DUST-PROOF FRAME, MATERIAL: ALUMINUM.
  - ③ 8X19 HOUSING MATES WITH CONTROLLER HOUSING MATERIAL: PBTUL94V-0(BLACK)
  - ④ CABLE, OUTER LAYER MATERIAL: PVCBG01RUBBER.
  - ⑤ GROUND LINE.
  - ⑥ GLASS BOARD, THICKNESS: 6.

CONNECTION CHART

PIN	SIGNAL	INSULATION COLOR
1	GND	OVERALL SHIELD
2	KEY	
3	Y-in2	BLUE
4	Yout	BLUE
5	Y-in1	BLACK
6	GND	YELLOW
7	GND	
8	GND	GREEN
9	X-in2	WHITE
10	Xout	RED
11	X-in1	RED
12	KEY	