



- Instruction:
- 1.Type: Film to Glass
 - 2.Operating Voltage: $\leq 10V$
 - 3.Response Time: $\leq 10ms$
 - 4.Storage Temperature: $-20^{\circ}C \sim +70^{\circ}C$
 - 5.Operation Temperature/Humidity: $-10^{\circ}C \sim +60^{\circ}C$ / 20%~95%
 - 6.Hitting Life: $>1,000,000$ Times $\sim 250gf$ Force;
 - 7.writing Life: $>100,000$ Times $250gf$ Force;
 - 8.Connect Material: FPC

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.1mm
- 11.Light transmission: $\geq 78\%$
- 12.Force: 100g or more
- 13.Linearity: $\leq 1.5\%$
- 14.Insulation: $\geq 20M\Omega$
- 15.Resistance: X: $180\Omega \sim 330\Omega$;
Y: $510\Omega \sim 900\Omega$;
- 16.Surface Hardness: $\geq 3H$ (pencil)

Touch-Pane-VTW4065A0

REVISIONS

NO	SCALE	1:1	MATERIAL	F/A	Version
001	UNIT	mm		2A	1.0
002	DESIGN	Author	DATE	20090720	
003	CHECK	Approver	DATE	20090720	
004	RELEASE	J	DATE	20090720	