MULTI-TOUCH G4

Q PQ Labs

Highlights

- True Multi-Touch (Detects over 32 points simultaneously)
- PQ Labs patented Infrared Cell Imaging Technology
- No Ghost Point
- Low Cost

PQ Labs Multi-Touch G4

PQ Labs multi-touch overlay is plug-and-play solution for both developers and end-users. Exceptional durability and accuracy.

WEB: http://www.pqlabs.com Email: contact@pqlabs.com © 2012 PQ Labs All rights reserved.

■ SPECIFICATION - PART 1

Available Sizes	 32", 40", 42", 46", 47", 50", 52", 55", 58", 60", 65", 70", 80", 84", 85" Customized sizes available upon request Two Sizes of 55" Diagonal: 54.6", most LCD TVs Diagonal: 55", for Plasma Two Sizes of 70" Diagonal: 69.59", most 70" TVs Diagonal: 70.25", Samsung 70" only
Detectable Touch Points	True Multi-Touch (Detects over 32 touch points simultaneously) G4 Plus: 32+(unlimited) Touch Points G4 Standard: 12 Touch Points G4 Basic: 6 Touch Points G4 Dual: 2 Touch Points
Glass	PQ Labs Mighty Glass • 32" – 47": 3 mm Mighty Glass • 50" – 84": 4 mm Mighty Glass Please contact our sales for 70" - 84" Mighty Glass
Operating System	 Windows 8/7/Vista/XP, Mac OS X, Ubuntu/Fedora Android (Fully support iStick, other Android devices need to be customized)
Sample Rate	Up to 200 fps (depends on frame size)
Finger Touch Accuracy	2.7 mm

■ SPECIFICATION - PART 2

Report Resolution	32768 x 32768
Waterproof	Anti-Spill (customizable to IP65 Waterproof)
Assembly Method	Smart Easy Assembly
Power Supply	5V / 4A power adapter
Data Interface	 USB 2.0 (Full speed), compatible with USB 3.0 / USB 1.1 port, HID compliant, plug-and-play compatible USB A Type Receptacle
Touch Method	 Finger, gloved hand or any other pointer Object shape recognition (Palm, fist recognitions)
Touch Activation Force	No pressure required
Touch Durability	Unlimited
Environment	 Operating temperature: 0 °C to 55 °C Storage temperature: -25 °C to 85 °C Operating humidity:10% to 90% RH, non-condensing Storage humidity: 10% to 90% RH, non-condensing