

# IR Frame Panel Specification

Part No.: SNT-IR-TFP-12.1

## Product Description

- 1. High Accuracy Infrared touch frame, Resolution by interpolation algorithm to 4096(W)\*4096(D)
- 2. Adapt to various application environments
- 3. Drive-free, plug and play

## Major Technical Specifications

Frame Material	Polycarbonate/Aluminum	
Color	Black	
Upper Frame Width	See the attached Drawing	
Bottom Frame Width	See the attached Drawing	
Frame Thickness	See the attached Drawing	
Cover Glass	Build-in 2-3mm Tempered Glass	
Resolution	4096(W)*4096(D)	
Response Time	≤15ms	
Touch Accuracy	$\pm 2$ mm	
Cursor Speed	120 dot/sec	
Output format	Coordinate Output	
Touch Times	Unlimited	
Touch Activation Force	Non Minimum Activation Force	
Ports Type	USB	

### 4. Electronic Features

Power Sup	USB Power 2	USB Power 2W(less than 500mA at DC 5V	
Voltage	DC+5V±5%		

#### 5. Environment Features

ITEM	Specs.	
Temperature Scope	Operating Temperature: 0°C~55°C	
	Warehousing Temperature: -20°C ~70°C	
Relative Humidity	nidity Operating Humidity: 10%~ 90% RH, no condensation	
	Warehousing Humidity: 10%∼ 90% RH, no condensation	
Light Resistance	With some level light resistance	
Water-Proof	Surface Water-proof (Optional IP65)	

Touch the World 让触摸感动世界



#### 6. Software Features

ITEM	Specs.	
Touch Type	10 Points Multi-touch	
OS Supported	Windows 7/8/10/Windows XP/Vista/Linux/Android	

## 7. Reliability

ITEM	Testing Conditions	Judgement
High-temperature/High	Temperature: 50°℃	Performs
Humidity Operating	Humidity: 85% no condensation	Normally
	Working Continuous 24 Hours	
Low-temperature	Temperature: -10 ℃ Perform	
Operating	Working Continuous 24 Hours	Normally
Low-temperature	Temperature: -20°C	Performs
Warehousing	Working Continuous 24 Hours, 2 hours in Normal indoor Temperature	Normally
High-temperature, High-	Temperature: 70°℃	Performs
Humidity Warehousing	Humidity: 90% no condensation	Normally
	Working Continuous 24 Hours, 2 hours in Normal indoor Temperature	
USB plug test	2000times each under windows 7 and windows XP	Performs
		Normally
System Restart	1000 times each under windows 7 and windows XP	Performs
		Normally
Basic Function	Signal and Line drawing and click	Performs
		Normally





## 8. Technical Drawing



