

X Slim Series

Multi-Touch Overlay

Features:

- True Multi-Touch, No Ghost Points:
Supports 6/10/16/32/40 Precise Touch Points Simultaneously
- Single USB Connection
- Extremely Low-cost
- Accurate and Reliable, Low Maintenance Requirements
- Landscape or Portrait Orientation
- Input: Finger, Gloved Hand or Stylus (with diameter $\geq 5\text{mm}$)
- Object Recognition (Palm, Fist etc.)
- Supports Multi-overlays Connecting to One PC
- One-Time Calibration, Friendly Interface
- Compatible with Windows 7/8, Mac OS X, Linux*
- Supports TUIO/Flash Protocol and Windows Native HID
- Available in Integration Kit Form and Easy DIY Installation

* ZaagTech utility program required.

Specifications:

Available sizes	21.5"-65"
Number of Touch Points	6/10/16/32/40 touch points
Frame Dimension	19mm width, 10.8mm thick (without glass)
Luminous transmission	95-100% typical with clear glass
Touch technology	Infrared
Touch Activation force	No pressure required
Touch resolution	32767×32767
Touch durability	Unlimited
Touch Response Time	Typical response time 7 - 13ms
Environment	Operating temperature: 0°C - 60°C; Storage temperature: -40°C - 85°C; Operating Humidity: 10% to 90% RH, non-condensing; Storage humidity: 10% to 90%RH, non-condensing
Power Supply	Single USB Connection Operating ≤ 750mW; Standing by ≤ 250mW
ESD	Per EN61000-4-21995; Level 4. Contact discharge 8kV, air discharge 15kV on USB connector pins
Certificates	FCC, CE, RoHS, IP65 Approved
EMC	EN55022, EN55024, CISPR 22, CISPR24
Interface	USB2.0 compatible with USB 1.1
Operating Systems	Windows 7/8, Mac OS X, Linux ¹
Connection options	Standard: USB Serial option: Custom DB9 cable (3m) (extendable to 100 meters)
Software	ZaagTech zinFrame Server
Warranty²	2 year parts and labor

1. ZaagTech utility program required.
2. Warranty for X slim series multi-touch overlay excludes coverage for damage resulting from accident, liquid damage, disassembly, unauthorized service and unauthorized modifications.